



## Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 330kVA

By Acme Electric  
Catalog # [DTGB03304S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 330kVA.



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA5

### General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB03304S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000793
Winding Material	AL
kVA	330

### Dimensions

Dimensions	35.5 in x 39.5 in x 45.6 in
Height	45.6 in
Length	35.5 in
Weight	2090 lb

Width 39.5 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

### Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

### Logistics

Carton Quantity	1
Pallet Quantity	1

### Product Assets

Brochures - Drive Isolation Transformers
Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing -
<a href="#">Acme_DTGB03304S_TECHNICAL_DRAWINGS</a>
SDS - HCC SDS
Specifications - DTGB03304S Specification Sheet French
Specifications - DTGB03304S
Specifications - DTGB03304S Specification Sheet
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand