



## Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 40kVA

By Acme Electric  
Catalog # [DTGB0404S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 40kVA.



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA1

### General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB0404S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	004750369547
Winding Material	AL
kVA	40

### Dimensions

Dimensions	19.37 in x 24.39 in x 25.5 in
Height	25.5 in
Length	19.37 in
Weight	395 lb

Width 24.39 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

### Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

### Logistics

Carton Quantity	1
Pallet Quantity	1

### Product Assets

[Brochures - Drive Isolation Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Engineering Drawing - Acme\\_DTGB0404S\\_TECHNICAL\\_DRAWINGS](#)  
[SDS - HCC SDS](#)  
[Specifications - DTGB0404S](#)  
[Specifications - DTGB0404S Specification Sheet](#)  
[Specifications - DTGB0404S Specification Sheet French](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand