



Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 63kVA

By Acme Electric
Catalog # [DTGB0634S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 63kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA2

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB0634S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000847
Winding Material	AL
kVA	63

Dimensions

Dimensions	22.37 in x 28.15 in x 29.9 in
Height	29.9 in
Length	22.37 in
Weight	550 lb

Width 28.15 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

Brochures - Drive Isolation Transformers
Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing -
Acme_DTGB0634S_TECHNICAL_DRAWINGS
SDS - HCC SDS
Specifications - DTGB0634S Specification Sheet
Specifications - DTGB0634S Specification Sheet French
Specifications - DTGB0634S
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
ACME_CA-DTGB0634S-SPEC-EN | REV 1/2025