



Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 660kVA

By Acme Electric
Catalog # [DTGB06604S](#)



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA6

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB06604S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503084281
Winding Material	AL
kVA	660

Dimensions

Dimensions	41.49 in x 54 in x 62.84 in
------------	-----------------------------

Height	62.84 in
Length	41.49 in
Weight	3700 lb
Width	54 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Product Assets

- [Brochures - Drive Isolation Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_DTGB06604S_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - DTGB06604S Specification Sheet French](#)
- [Specifications - DTGB06604S Specification Sheet](#)
- [Specifications - DTGB06604S](#)
- [Terms and Conditions - HCC Terms & Conditions](#)