



## Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 770kVA

By Acme Electric  
Catalog # [DTGB07704S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 770kVA.



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA6

### General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB07704S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000854
Winding Material	AL
kVA	770

### Dimensions

Dimensions 41.49 in x 54 in x 62.84 in

Height	62.84 in
Length	41.49 in
Weight	3600 lb
Width	54 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

### Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

### Product Assets

[Brochures - Drive Isolation Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Engineering Drawing - Acme\\_DTGB07704S\\_TECHNICAL\\_DRAWINGS](#)  
[SDS - HCC SDS](#)  
[Specifications - DTGB07704S](#)  
[Specifications - DTGB07704S Specification Sheet](#)  
[Specifications - DTGB07704S Specification Sheet French](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand