



Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 7.5kVA

By Acme Electric
Catalog # [DTGB72S](#)



Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 7.5kVA.

Features

- Copper terminations for trouble free operation
- Wound Core and Strip Winding for Low Losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units

General

ANFC Taps	1
BNFC Taps	1
Catalog Number	DTGB72S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	5%
UL Insulation Class	180°C
UPC	047503088234
Winding Material	AL
kVA	7.5

Dimensions

Dimensions	7.37 in x 19.25 in x 15.21 in
Height	15.21 in
Length	7.37 in
Weight	180 lb

Width 19.25 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	8

Product Assets

Brochures - Drive Isolation Transformers
Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing -
Acme_DTGB72S_TECHNICAL_DRAWINGS
SDS - HCC SDS
Specifications - DTGB72S Specification Sheet
Specifications - DTGB72S Specification Sheet French
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand