



Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 275kVA

By Acme Electric
Catalog # [DTHB002754S](#)

Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 275kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA5

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTHB002754S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	575Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503091098
Winding Material	AL
kVA	275

Dimensions

Dimensions 35.5 in x 39.5 in x 45.6 in

Height	45.6 in
Length	35.5 in
Weight	2090 lb
Width	39.5 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	575D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Product Assets

- [Brochures - Drive Isolation Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing -](#)
- [Acme_DTHB002754S_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - DTHB002754S](#)
- [Specifications - DTHB002754S Specification Sheet](#)
- [Specifications - DTHB002754S Specification Sheet French](#)
- [Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand