



Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 20kVA

By Acme Electric
Catalog # [DTHB0202S](#)

Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 20kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound Core and Strip Winding for Low Losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units

General

ANFC Taps	1
BNFC Taps	1
Catalog Number	DTHB0202S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	575Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	5%
UL Insulation Class	180°C
UPC	047503000984
Winding Material	AL
kVA	20

Dimensions

Dimensions	10.18 in x 20.94 in x 20.77 in
Height	20.77 in
Length	10.18 in
Weight	435 lb

Width 20.94 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	575D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	4

Product Assets

Brochures - Drive Isolation Transformers
Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing -
Acme_DTHB0202S_TECHNICAL_DRAWINGS
SDS - HCC SDS
Specifications - DTHB0202S Specification Sheet
Specifications - DTHB0202S Specification Sheet French
Specifications - DTHB0202S
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand