



## Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 51kVA

By Acme Electric  
Catalog # [DTHB0514S](#)

Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 51kVA.



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA2

### General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTHB0514S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	575Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503089507
Winding Material	AL
kVA	51

### Dimensions

Dimensions	22.37 in x 28.15 in x 29.9 in
Height	29.9 in
Length	22.37 in
Weight	400 lb

Width 28.15 in

### Electrical Ratings

Frequency Rating 60 Hz  
Primary Voltage 575D V

### Certifications And Compliance

CSA Standard C22.2 No. 47  
Nema Rating NEMA 2  
UL Standard UL 1561

### Logistics

Carton Quantity 1  
Pallet Quantity 1

### Product Assets

[Brochures - Drive Isolation Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Engineering Drawing - Acme\\_DTHB0514S\\_TECHNICAL\\_DRAWINGS](#)  
[SDS - HCC SDS](#)  
[Specifications - DTHB0514S](#)  
[Specifications - DTHB0514S Specification Sheet](#)  
[Specifications - DTHB0514S Specification Sheet French](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
ACME\_CA-DTHB0514S-SPEC-EN | REV 1/2025