



Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 550kVA

By Acme Electric
Catalog # [DTHB05504S](#)

Drive Isolation Transformer - Three Phase, 575Δ - 460Y/266V, 550kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA7

General

| | |
|----------------------|-----------------------------|
| ANFC Taps | 2 |
| BNFC Taps | 2 |
| Catalog Number | DTHB05504S |
| Construction | Ventilated |
| Electrostatic Shield | Shielded |
| Max Temperature Rise | 150 Degrees Celsius |
| Mounting Type | Floor |
| Primary Voltage | 575Δ |
| Product Category | Drive Isolation Transformer |
| Secondary Voltage | 460Y/266 V |
| Taps % Steps | 2.5% |
| UL Insulation Class | 220°C |
| UPC | 047503089477 |
| Winding Material | AL |
| kVA | 550 |

Dimensions

| | |
|------------|-------------------------------|
| Dimensions | 41.49 in x 45.5 in x 57.84 in |
| Height | 57.84 in |
| Length | 41.49 in |
| Weight | 3000 lb |

Width 45.5 in

Electrical Ratings

| | |
|------------------|--------|
| Frequency Rating | 60 Hz |
| Primary Voltage | 575D V |

Certifications And Compliance

| | |
|--------------|--------------|
| CSA Standard | C22.2 No. 47 |
| Nema Rating | NEMA 2 |
| UL Standard | UL 1561 |

Logistics

| | |
|-----------------|---|
| Carton Quantity | 1 |
| Pallet Quantity | 1 |

Product Assets

| |
|---|
| Brochures - Drive Isolation Transformers |
| Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors |
| Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice |
| Engineering Drawing - |
| Acme_DTHB05504S_TECHNICAL_DRAWINGS |
| SDS - HCC SDS |
| Specifications - DTHB05504S Specification Sheet |
| Specifications - DTHB05504S Specification Sheet French |
| Specifications - DTHB05504S |
| Terms and Conditions - HCC Terms & Conditions |



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
ACME_CA-DTHB05504S-SPEC-EN | REV 1/2025