



Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V, 500VA

By Acme Electric
Catalog # [T181051](#)

Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V, 500VA.

Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

General

Catalog Number	T181051
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	120 X 240 V
Product Category	Buck-Boost Transformer
Secondary Voltage	12/24 V
UL Insulation Class	180°C
UPC	047503084489
Winding Material	CU
kVA	0.5

Dimensions

Dimensions	4.2 in x 4.37 in x 9.06 in
Height	9.06 in
Length	4.2 in
Weight	15 lb
Width	4.37 in

Electrical Ratings



Frequency Rating	50/60 Hz
Primary Voltage	120 X 240 V

Certifications And Compliance

CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	32

Product Assets

- [Brochures - Buck-Boost Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 7 - Buck Boost Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_BB2_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - T181051 Specification Sheet](#)
- [Specifications - T181051](#)
- [Specifications - T181051 Specification Sheet French](#)
- [Terms and Conditions - HCC Terms & Conditions](#)
- [Video - Product Information Video Series - Buck Boost Transformers](#)