



Buck-Boost Transformer - Single Phase, 120 X 240 - 16/32V, 100VA

By Acme Electric
Catalog # [T181055](#)

Buck-Boost Transformer - Single Phase, 120 X 240 - 16/32V, 100VA.

Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

General

Catalog Number	T181055
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	120 X 240 V
Product Category	Buck-Boost Transformer
Secondary Voltage	16/32 V
UL Insulation Class	180°C
UPC	047503086834
Winding Material	CU
kVA	0.1

Dimensions

Dimensions	3.67 in x 3.89 in x 7.16 in
Height	7.16 in
Length	3.67 in
Weight	5 lb
Width	3.89 in

Electrical Ratings



*Representative Image

Frequency Rating	50/60 Hz
Primary Voltage	120 X 240 V

Certifications And Compliance

CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	3
-----------------	---

Product Assets

- [Brochures - Buck-Boost Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 7 - Buck Boost Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_BB1_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - T181055](#)
- [Specifications - T181055](#)
- [Specifications - T181055 Specification Sheet](#)
- [Terms and Conditions - HCC Terms & Conditions](#)
- [Video - Product Information Video Series - Buck Boost Transformers](#)