



# Buck-Boost Transformer - Single Phase, 240 X 480 - 24/48V, 50VA

By Acme Electric  
Catalog # T181061

Buck-Boost Transformer - Single Phase, 240 X 480 - 24/48V, 50VA.

## Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

## General

Catalog Number	T181061
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Buck-Boost Transformer
Secondary Voltage	24/48 V
UL Insulation Class	180°C
UPC	047503087503
Winding Material	CU
kVA	0.05

## Dimensions

Dimensions	4.51 in x 4.75 in x 9.68 in
Height	9.68 in
Length	4.51 in
Weight	4 lb
Width	4.75 in



## Electrical Ratings

Frequency Rating	50/60 Hz
Primary Voltage	240 X 480 V

## Certifications And Compliance

CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

## Logistics

Carton Quantity	3
-----------------	---

## Product Assets

[Brochures - Buck-Boost Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 7 - Buck Boost Transformers](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[SDS - HCC SDS](#)  
[Specifications - T181061](#)  
[Specifications - T181061 Specification Sheet](#)  
[Specifications - T181061](#)  
[Terms and Conditions - HCC Terms & Conditions](#)  
[Video - Product Information Video Series - Buck Boost Transformers](#)