



Buck-Boost Transformer - Single Phase, 240 X 480 - 24/48V, 150VA

By Acme Electric
Catalog # [T181063](#)

Buck-Boost Transformer - Single Phase, 240 X 480 - 24/48V, 150VA.

Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

General

Catalog Number	T181063
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Buck-Boost Transformer
Secondary Voltage	24/48 V
UL Insulation Class	180°C
UPC	047503183502
Winding Material	CU
kVA	0.15

Dimensions

Dimensions	5.13 in x 5.5 in x 11.62 in
Height	11.62 in
Length	5.13 in
Weight	7 lb
Width	5.5 in

Electrical Ratings



Frequency Rating	50/60 Hz
Primary Voltage	240 X 480 V

Certifications And Compliance

CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	3
-----------------	---

Product Assets

- [Brochures - Buck-Boost Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 7 - Buck Boost Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_BB1_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - T181063](#)
- [Specifications - T181063](#)
- [Specifications - T181063 Specification Sheet](#)
- [Terms and Conditions - HCC Terms & Conditions](#)
- [Video - Product Information Video Series - Buck Boost Transformers](#)