



# Low Voltage Distribution Transformer - Single Phase, 600 - 120V/240V, 2kVA

By Acme Electric  
Catalog # [T253112S](#)



Low Voltage Distribution Transformer - Single Phase, 600 - 120V/240V, 2kVA.

## Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

## General

Catalog Number	T253112S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	600
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
UL Insulation Class	180°C
UPC	047503732809
Winding Material	CU
kVA	2

## Dimensions

Dimensions	5.13 in x 5.5 in x 13 in
Height	13 in
Length	5.13 in
Weight	38 lb
Width	5.5 in

## Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	600 V

## Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

## Logistics

Carton Quantity	1
Pallet Quantity	20

## Product Assets

- [Brochures - General Purpose Dry-Type Distribution Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Customer Use Drawings - a-102758](#)
- [Customer Use Drawings - a-125860](#)
- [Engineering Drawing - T253112S](#)
- [SDS - HCC SDS](#)
- [Specifications - T253112S Specification Sheet French](#)
- [Specifications - T253112S](#)
- [Specifications - T253112S Specification Sheet](#)
- [Terms and Conditions - HCC Terms & Conditions](#)