



Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 7.5kVA

By Acme Electric
Catalog # [T2535153S](#)

Low Voltage Distribution Transformer - Single Phase, 240X480
- 120/240V, 7.5kVA



*Representative Image

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

ANFC Taps	2
BNFC Taps	2
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	180°C
UPC	047503734056
Winding Material	AL
kVA	7.5

Dimensions

Dimensions	10.84 in x 13.5 in x 15.19 in
Height	15.19 in
Length	10.84 in
Weight	115 lb
Width	13.5 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 X 480 V

Certifications and Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Product Assets

[3D Models - Group_24](#)

[Brochures - General Purpose Dry-Type Distribution Transformers](#)

[Brochures - International Transformers](#)

[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)

[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)

[Customer Use Drawings - a-102722-b](#)

[Customer Use Drawings - a-125852](#)

[Customer Use Drawings - a-125877](#)

[Customer Use Drawings - a-125893](#)

[Customer Use Drawings - a-125885](#)

[Customer Use Drawings - a-700322](#)

[Customer Use Drawings - a-125883](#)

[Customer Use Drawings - a-125873](#)

[Customer Use Drawings - a-125881](#)

[Engineering Drawing - T2535153S](#)

[Installation Manuals - Acme Electric Manual A](#)

[SDS - HCC_SDS](#)

[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
ACME_T2535153S_SPEC | REV 3/2023