



# Low Voltage Distribution Transformer - Three Phase, 600/480 - 480/380V, 300/240kVA, Autotransformer

By Acme Electric  
Catalog # [T2A527171](#)



\*Representative Image

Low Voltage Distribution Transformer - Three Phase, 600/480 - 480/380V, 300/240kVA, Autotransformer.

## Features

- Quiet operation with sound levels below NEMA standards
- Optional weather shield - WSA2

## General

BNFC Taps	2
Catalog Number	T2A527171
Construction	Ventilated
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	600/480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	480/380 V
Taps % Steps	5.0%
UL Insulation Class	220°C
UPC	047503420171
Winding Material	AL
kVA	300/240

## Dimensions

Dimensions	22.37 in x 28.15 in x 29.41 in
Height	29.41 in
Length	22.37 in
Weight	650 lb
Width	28.15 in

## Electrical Ratings

Frequency Rating	50/60 Hz
Primary Voltage	600/480 V

## Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

## Logistics

Carton Quantity	1
Pallet Quantity	1

## Product Assets

- [Brochures - General Purpose Dry-Type Distribution Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - T2A527171](#)
- [SDS - HCC SDS](#)
- [Specifications - T2A527171 Specification Sheet](#)
- [Specifications - T2A527171 Specification Sheet French](#)
- [Specifications - T2A527171](#)
- [Terms and Conditions - HCC Terms & Conditions](#)