



Low Voltage Distribution Transformer - Three Phase, 600/480 - 480/380V, 500/400kVA, Autotransformer

By Acme Electric
Catalog # [T2A527191](#)



*Representative Image

Low Voltage Distribution Transformer - Three Phase, 600/480 - 480/380V, 500/400kVA, Autotransformer.

Features

- Quiet operation with sound levels below NEMA standards
- Optional weather shield - WSA3

General

BNFC Taps	2
Catalog Number	T2A527191
Construction	Ventilated
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	600/480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	480/380 V
Taps % Steps	5.0%
UL Insulation Class	220°C
UPC	047503420195
Winding Material	AL
kVA	500/400

Dimensions

Dimensions	26.88 in x 31.9 in x 35.47 in
Height	35.47 in
Length	26.88 in
Weight	790 lb
Width	31.9 in

Electrical Ratings

Frequency Rating	50/60 Hz
Primary Voltage	600/480 V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - T2A527191](#)
[SDS - HCC SDS](#)
[Specifications - T2A527191](#)
[Specifications - T2A527191 Specification Sheet](#)
[Specifications - T2A527191 Specification Sheet French](#)
[Terms and Conditions - HCC Terms & Conditions](#)