



Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 6kVA

By Acme Electric
Catalog # [T2A533091S](#)



*Representative Image

Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 6kVA.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T2A533091S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	480Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503733554
Winding Material	AL
kVA	6

Dimensions

Dimensions	8.82 in x 14.17 in x 11.83 in
Height	11.83 in
Length	8.82 in
Weight	140 lb

Width 14.17 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	6

Product Assets

- [Brochures - General Purpose Dry-Type Distribution Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - T2A533091S](#)
- [SDS - HCC SDS](#)
- [Specifications - T2A533091S Specification Sheet French](#)
- [Specifications - T2A533091S](#)
- [Terms and Conditions - HCC Terms & Conditions](#)