



Low Voltage Distribution Transformer - Three Phase, 480Δ - 240Δ120V, 9kVA

By Acme Electric
Catalog # [T2A533401S](#)

Low Voltage Distribution Transformer - Three Phase, 480Δ - 240Δ120V, 9kVA.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T2A533401S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	480Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	240D 120 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503733806
Winding Material	AL
kVA	9

Dimensions

Dimensions	11.52 in x 17.77 in x 14.03 in
Height	14.03 in
Length	11.52 in
Weight	180 lb
Width	17.77 in



*Representative Image

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	4

Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - T2A533401S](#)
[SDS - HCC SDS](#)
[Specifications - T2A533401S](#)
[Specifications - T2A533401S Specification Sheet French](#)
[Specifications - T2A533401S Specification Sheet](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand