



Low Voltage Distribution Transformer - Three Phase, 600Δ - 480Y/277V, 3kVA

By Acme Electric
Catalog # [T2A795161S](#)

Low Voltage Distribution Transformer - Three Phase, 600Δ - 480Y/277V, 3kVA.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T2A795161S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	600Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	480Y/277 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503420508
Winding Material	CU
kVA	3

Dimensions

Dimensions	7.47 in x 12.37 in x 10.38 in
Height	10.38 in
Length	7.47 in
Weight	75 lb



*Representative Image

Width 12.37 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	600D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	9

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing - T2A795161S
SDS - HCC SDS
Specifications - T2A795161S Specification Sheet
Specifications - T2A795161S
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
ACME_CA-T2A795161S-SPEC-EN | REV 1/2025