



Non Linear Load Transformer - Three Phase, 480Δ - 208Y/120V, 15kVA, K4

By Acme Electric
Catalog # [T3015K0013BK4S](#)



Non Linear Load Transformer - Three Phase, 480Δ - 208Y/120V, 15kVA, K4.

Features

- Copper terminations for trouble free operation
- Wound Core and Strip Winding for Low Losses
- Electrostatic shield for enhanced protection

General

ANFC Taps	2
BNFC Taps	4
Catalog Number	T3015K0013BK4S
Construction	Ventilated
Electrostatic Shield	Shielded
K Factor	4
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	480Δ
Product Category	Non Linear Load Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503093795
Winding Material	AL
kVA	15

Dimensions

Dimensions	19.37 in x 24.39 in x 25.5 in
Height	25.5 in
Length	19.37 in
Weight	300 lb
Width	24.39 in

Electrical Ratings

Efficiency	97.89%
Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Dept of Energy Regulation	Meets or exceed U.S. DOE 10 CFR Part 431
Nema Rating	NEMA 3R
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

Brochures - Non-Linear Load Transformers
Catalogs - Acme Electric Catalog - Section 3 - Harmonic
Mitigating & Load Isolation Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing - T3015K0013BK4S
SDS - HCC SDS
Specifications - T3015K0013BK4S Specification Sheet French
Specifications - T3015K0013BK4S Specification Sheet
Specifications - T3015K0013BK4S
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand