



Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 30kVA

By Acme Electric
Catalog # [T3030K0013B](#)



Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 30kVA.

Features

- Quiet operation with sound levels below NEMA standards

General

ANFC Taps	2
BNFC Taps	4
Catalog Number	T3030K0013B
Construction	Ventilated
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	480Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503091128
Winding Material	AL
kVA	30

Dimensions

Dimensions	19.37 in x 24.39 in x 25.5 in
Height	25.5 in
Length	19.37 in
Weight	290 lb
Width	24.39 in

Electrical Ratings

Efficiency	98.23%
Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Dept of Energy Regulation	Meets or exceed U.S. DOE 10 CFR Part 431
Nema Rating	NEMA 3R
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - T3030K0013B](#)
[SDS - HCC SDS](#)
[Specifications - T3030K0013B Specification Sheet French](#)
[Specifications - T3030K0013B Specification Sheet](#)
[Specifications - T3030K0013B](#)
[Terms and Conditions - HCC Terms & Conditions](#)