


Primary Volts	Connect Primary Lines To	Inter-Connect	Connect Secondary Lines To
218	X1, X2, X3	1	
213	X1, X2, X3	2	
208	X1, X2, X3	3	
203	X1, X2, X3	4	
198	X1, X2, X3	5	

Secondary Volts			
480			H1, H2, H3
277 1 phase			H1 to H0 H2 to H0 H3 to H0

NOTE:
PRIMARY AND SECONDARY BUS AREA
IN FRONT OF CASE.

REVISIONS

NOTES:

1. Dry Type
2. Class AA
3. Ventilated
4. Paint - #61 ANSI



KVA	CATALOG NUMBER	VOLTAGE		LUG KIT	WEIGHT	PHASE	FREQUENCY
		LOW	HIGH				
45	T3045K0034B	208Δ	480Y/277		500 Lbs	3φ	60Hz
Temp Rise:		150°C	TYPICAL PERFORMANCE DATA			Typical Efficiency @ 35%	98.48%
Insulation:		220°C				Typical No Load Losses:	139.79
NEMA ST20 Standard:		45 dB	Regulation @ 100% PF	2.20%	Windings:	AL	100% Load (Typ) Load Losses (I²R)
Electrostatic Shield:		Option	Standards:	UL/CSA	Impedance:	4.25%	1107.44
			Approvals:	DOE-2016	Enclosure:	3R	Total Load Losses:
							1247.23

Meets US DOE 2016 Efficiency

DATE: 14-Aug-13

TYPE NO:

CASE 1