





KEY: DENOTES CONDUIT AREAS



Primary Volts	Connect Primary Lines To	Inter-Connect	Connect Secondary Lines To
504	H1, H2, H3	1	
492	H1, H2, H3	2	
480	H1, H2, H3	3	
468	H1, H2, H3	4	
456	H1, H2, H3	5	
444	H1, H2, H3	6	
432	H1, H2, H3	7	
Secondary Volts			
240			X1, X2, X3
120			X1, X4 or X2, X4

NOTE: PRIMARY AND SECONDARY BUS AREA IN FRONT OF CASE.

KVA	CATALOG NUMBER	VOLTAGE		LUG KIT	WEIGHT	PHASE	FREQUENCY
		HIGH	LOW				
75	T3075K0023B	480Δ	240Δ/120		600 Lbs	3φ	60Hz
Temp Rise:		150°C	TYPICAL PERFORMANCE DATA			Typical Efficiency @ 35%	98.66%
Insulation:		220°C				Typical No Load Losses:	153.53
NEMA ST20 Standard:	50 dB	Regulation @ 100% PF	2.90%	Standards:	UL/CSA	100% Load (Typ) Load Losses (I ² R)	2244.87
Electrostatic Shield:	Option	Approvals:	DOE-2016	Windings:	AL	Total Load Losses:	2398.40
				Impedance:	5.60%		
				Enclosure:	3R		

Meets US DOE 2016 Efficiency

REVISIONS

NOTES:

1. Dry Type
2. Class AA
3. Ventilated
4. Paint - #61 ANSI



DATE: 14-Aug-13

TYPE NO:

CASE 2