





KEY: DENOTES CONDUIT AREAS

NOTE: PRIMARY AND SECONDARY BUS AREA IN FRONT OF CASE.



Primary Volts	Connect Primary Lines To	Inter-Connect	Connect Secondary Lines To
504	H1, H2, H3	1	
492	H1, H2, H3	2	
480	H1, H2, H3	3	
468	H1, H2, H3	4	
456	H1, H2, H3	5	
444	H1, H2, H3	6	
432	H1, H2, H3	7	

Secondary Volts			
240			X1, X2, X3
120			X1, X4 or X2, X4

REVISIONS

NOTES:

1. Dry Type
2. Class AA
3. Ventilated
4. Paint - #61 ANSI



KVA	CATALOG NUMBER		VOLTAGE		LUG KIT	WEIGHT	PHASE	FREQUENCY
			HIGH	LOW				
112.5	T3112K0023B		480Δ	240Δ/120		938 Lbs	3φ	60Hz
Temp Rise:		150°C	TYPICAL PERFORMANCE DATA				Typical Efficiency @ 35%	98.80%
Insulation:		220°C					Typical No Load Losses:	273.43
NEMA ST20 Standard:		50 dB	Regulation @ 100% PF	1.90%	Standards:	UL/CSA	100% Load (Typ) Load Losses (I²R)	2216.92
Electrostatic Shield:		Option	Approvals:	DOE-2016	Windings:	AL	Total Load Losses:	2490.35
					Impedance:	3.92%		
					Enclosure:	3R		

Meets US DOE 2016 Efficiency

DATE: 14-Aug-13

TYPE NO:

CASE 3