



Low Voltage Distribution Transformer - Three Phase, 480Δ - 240Δ120V, 15kVA

By Acme Electric
Catalog # [T3533411S](#)



Low Voltage Distribution Transformer - Three Phase, 480Δ - 240Δ120V, 15kVA.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T3533411S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	480Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	240D 120 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503733851
Winding Material	AL
kVA	15

Dimensions

Dimensions	9.03 in x 20.3 in x 18.86 in
Height	18.86 in
Length	9.03 in
Weight	250 lb
Width	20.3 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	4

Product Assets

- [Brochures - General Purpose Dry-Type Distribution Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - T3533411S](#)
- [SDS - HCC SDS](#)
- [Specifications - T3533411S Specification Sheet French](#)
- [Specifications - T3533411S Specification Sheet](#)
- [Specifications - T3533411S](#)
- [Terms and Conditions - HCC Terms & Conditions](#)