



Low Voltage Distribution Transformer - Three Phase, 480? - 208Y/120V, 30kVA, Encapsulated

By Acme Electric
Catalog # [T3793123S](#)

Low Voltage Distribution Transformer - Three Phase, 480? -
208Y/120V, 30kVA, Encapsulated

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

ANFC Taps	2
BNFC Taps	4
Catalog Number	T3793123S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	480 Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	2.5%
UL Insulation Class	180°C
UPC	047503183007
Winding Material	AL
kVA	30

Dimensions

Dimensions	11.14 in x 27.13 in x 24.81 in
Height	24.81 in
Length	11.14 in
Weight	613 lb



Oh No!
IMAGE COMING SOON

Width 27.13 in

Electrical Ratings

Frequency Rating 60 Hz
Primary Voltage 480D V

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - T3793123S](#)
[SDS - HCC SDS](#)
[Specifications - T3793123S](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand