



Low Voltage Distribution Transformer - Three Phase, 240Δ - 480Y/277V, 15kVA

By Acme Electric
Catalog # [T3796931S](#)



Low Voltage Distribution Transformer - Three Phase, 240Δ - 480Y/277V, 15kVA.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T3796931S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	240Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	480Y/277 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503796931
Winding Material	AL
kVA	15

Dimensions

Dimensions	9.03 in x 20.3 in x 18.86 in
Height	18.86 in
Length	9.03 in
Weight	245 lb
Width	20.3 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	4

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type
Distribution Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm
Notice
Engineering Drawing - T3796931S
SDS - HCC SDS
Specifications - T3796931S
Specifications - T3796931S Specification Sheet French
Specifications - T3796931S Specification Sheet
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand