



## Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 250kVA

By Acme Electric  
Catalog # [TP530243S](#)

Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 250kVA



\*Representative Image

### Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection
- Optional weather shield - WSA5

### General

ANFC Taps	2
BNFC Taps	4
Catalog Number	TP530243S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503090831
Winding Material	AL
kVA	250

### Dimensions

Dimensions	35.5 in x 39.5 in x 45.6 in
Height	45.6 in
Length	35.5 in

Weight 1440 lb  
Width 39.5 in

### Electrical Ratings

Frequency Rating 60 Hz  
Primary Voltage 240 X 480 V

### Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 506

### Logistics

Carton Quantity	1
Pallet Quantity	1

### Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Engineering Drawing - TP530243S](#)  
[SDS - HCC SDS](#)  
[Specifications - TP530243S](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand