

Catalog Number: S12/M16/B
Product ID: 7TCA296010R0027
EAN Number: 05020963003417
Status: Active



Representative

Nickel Plated Brass Straight Fitting with Swivel External Threads, Nominal Conduit Size 12 Millimeters, Metric Thread Size M16

North American Specifications (UNSPSC)

| | |
|-------------|--|
| UNSPSC | 39121311 Electrical fittings |
| IGCC | 4441 Electrical fittings |
| Brand Name | Adaptaflex |
| Type | Conduit Fitting with Metric Threads |
| Application | For Insertion into Threaded Entries or Knockout to Connect Conduit |
| Size | 5/16 Inch |
| Material | Brass |
| Finish | Nickel Plated |
| Color | Metallic |
| Connection | Straight |
| Cable Entry | M16 Thread |

European Specifications (ETIM)

| | |
|---|--|
| ETIM | EC001180 Screw connection for protective metallic hose |
| Nominal diameter | 12mm |
| Degree of protection (IP) conduit dependant | IP40-IP40 |
| Model | Straight |
| Revolving thread | Y |
| Construction type | External thread |
| Connection type screw connection to housing | Thread |
| Thread type | Metric |
| Thread connection size | M16 x 1.5 |
| One-piece | Y |
| Material housing | Brass |
| Surface protection | Nickel-plated |
| Thread length | 8mm |
| Total length | 29.5mm |
| Approved in combination with protective conduit DIN EN 61386-23 | N |
| Approved in combination with protective conduit CSA | N |
| Approved in combination with protective conduit UL | N |
| Approved in combination with protective conduit FI | N |
| Operating temperature | -50-+350°C |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 1x1x1 |
| Weight Uom | 0.06 lbs. Each |

Header

| | |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com