Thomas@Betts



Actual

 Catalog Number:
 SPLHCB25/25M

 Product ID:
 7TCA296100R0171

 EAN Number:
 05020963011023

Status: Active

Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Overbraid, Medium Flexibility, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

- Very high UV resistance
- · Very high flexibility
- · Very high fatigue life
- High mechanical strength, high abrasion resistance
- · Self extinguishing and halogen free
- Standard EMI screen rate
- Rail/Infrastructure
- Underground
- Public Buildings

North American Specifications (UNSPSC)	
UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Adaptaflex
Туре	Extreme Temperature Flexible Conduit
Application	Liquid Tight - Extreme Temperature Environments
Trade Size	3/4 Inch/NC 25mm
Outside Diameter	26.4mm
Inside Diameter	21.0mm
Length	25 Meters
Radius	110mm
Flexibility	Medium
Material	Galvanized Steel Core with Thermoplastic Rubber
	Cover
Color	Black

European Specifications (ETIM)	
ETIM	EC001179 Protective metallic hose
Nominal diameter	25mm
Outer diameter	26.4mm
Inner diameter	21mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Other
Sheathing material 2nd coating (exterior)	Stainless steel wire
Operating temperature	-65-+135°C
Degree of protection (IP)	IP68
Weight	0.487kg/m
Colour	Black
Bending strength	Flexible

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	1x1x1



Weight Uom 26.84 lbs. Each

Header

3D Model Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com