

Mercmaster™ Jr. Luminaire Mounting Hoods and Outlet Boxes

High Pressure Sodium. Suitable for Use in Wet Locations

UNILETS® for Use with Threaded Metal Conduit. 120 V Integral Ballast. Medium Base Socket for Medium Base Lamps.

		Hub Size (Inches)	Catalog Number	
			Aluminum	Malleable Iron
Pendant Mounting Furnished with connection block, gasket and screws				
 VMA  VA		1/2	—	VA50
		3/4	VMA75	VA75
		1	VMA100	VA100
Ceiling Mounting Five Hubs. Furnished with connection block, gasket, screws and four close-up plugs				
 VXHA		1/2	VXHA50-A	VXHA50
		3/4	VXHA75-A	VXHA75
		1	VXHA100-A	VXHA100
Cast/Outlet Box Mounting Furnished with connection block, mounting plate and gasket. Octagonal outlet box not suitable for classified locations. Fits SEH and 3-1/4" or 4" Octagonal Box ②				
 OBWW  OBV	Wall ⑤		OBVW1-A	OBVW1
	Ceiling		OBV1-A	OBV1
GS Round Base – Fits GSU Cast Boxes ③ ④ Furnished with connection block, gasket and screws				
 GSW  GS	Wall ⑤		—	GSW2
	Ceiling		—	GS2
JB Round Base – Fits JBX Cast Boxes ③ ④ Furnished with connection block, gasket and screws				
 JBW  JB	Wall ⑤		JBW1-A	JBW1
	Ceiling		JB1-A	JB1
Stanchion Mounting ⑥ 25° Stanchion furnished with connection block and screws.				
 MS		1-1/4	MS-125	—
		1-1/2	MS-150	—
JBX Cast Conduit Outlet Boxes ⑥				
 JBX		1/2	JBX50L-A	—
	Aluminum. 1-5/16" inside depth. Four tapped openings, two close-up plugs and mounting lugs. Use with JBW wall mount fixture and JB round base mounting hoods	3/4	JBX75L-A	—
GSU Cast Conduit Outlet Box (Form 20) ⑥				
 GSU-20  GSU-100		1/2 or 3/4	—	GSU-20
	Malleable iron. 1-3/4" inside depth. Four 3/4" hubs with four 3/4" to 1/2" reducers, and three 1/2" close-up plugs. Use with GSW wall mount fixture and GS round base mounting hoods	1	—	GSU-100

② Order SEH box from catalog section A and octagonal box from Section OB. To order fixture with guard, add G before voltage (example: MOB35G-120).

③ Order JBX below. Using JBX Box with these fixtures and mounting hoods provides 15/16" clearance from wall with refractor and 1-5/8" clearance from wall with globe.

④ Order GSU below. Using GSU Box with these fixtures and mounting hoods provides 1-5/16" clearance from wall with refractor and 2" clearance from wall with globe.

⑤ Reflectors cannot be used with wall mount fixtures. See dimensions for globe or refractor clearance from wall for these fixtures.

⑥ Stanchion mounting hood can be used with standard dome or 30° angle reflector.