



Representative

Catalog Number: AC 500 R 400 TN
Product ID: 7TAA262050R0092
UPC Number: 78378669183
Status: Active

Tin-Plated Aluminum Compression Reducer for Aluminum and Copper, 500 to 400 KCMIL

- Made of Aluminum for High Strength and High Conductivity.
- Dual-Rated for Use with Aluminum and Copper Conductors.
- Connector Bores Coated with Oxide Inhibitor and Capped to Prevent Oxidation.
- All Splices Marked with Conductor Size and Die Reference for Easy Identification.
- Meets or Exceeds ANSI C119.4 Specifications.

North American Specifications (UNSPSC)

UNSPSC	39121448 Wire or cable compression connector
IGCC	4668 Wire or cable compression connector
Brand Name	Blackburn
Type	Straight Compression Reducing Splice
Special Features	Dual Rated for Aluminum or Copper Conductors. Prefilled with Oxide Inhibiting Compound. Solid Center Stop ensures proper Cable insertion.
Application	Reducing Cable Splice
Standard	ANSI C119.4
Size	8-7/8 inch
Conductor Range	500 to 400
Material	Aluminum
Finish	Tin-Plated
Insulation	No

Packaging

Outer Quantity	25
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

Documents / Support Tools

Safety Data Sheet (SDS) Global	SDS-00041-TB2
--------------------------------	---------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com