



Locking Devices, Bryant Midget Locking, Industrial, Flanged Receptacle, 15A 125V, 2-Pole 2-Wire Non Grounding, ML-1R, Screw Terminal, Black

By Bryant
Catalog # 7468N



Locking Devices, Bryant Midget Locking, Industrial, Flanged Receptacle, 15A 125V, 2-Pole 2-Wire Non Grounding, ML-1R, Screw Terminal, Black

Features

- Industrial
- Flanged Receptacle
- 15A 125V
- 2-Pole 2-Wire Non Grounding
- ML-1R

Application

Extra Heavy Duty Industrial Specification Grade

General

Catalog Number	7468N
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	15A Midget Flanged Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Style	Non-Grounding
Type	Flanged Receptacle
UPC	781786638525

Dimensions

Dimensions	1.63 in x 1.38 in x 1.18 in
Display Size	Midget Locking

Height	1.18 in
Length	1.63 in
Width	1.38 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current Rating	15 A
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125V

Conductor Related

Number Of Wires	2-Wire
Wire Size	#18 AWG to #12 AWG

Certifications And Compliance

Nema Rating	ML-1R
-------------	-------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalogs - Bryant Full Line Catalog](#)
- [Specifications - 7468N Specification Sheet English](#)
- [Specifications - 7468N Specification Sheet French](#)