

Locking Devices, Twist-Lock®, Economy, Receptacle, 50A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non- NEMA, Screw Terminal, Black

By Hubbell Wiring Device-Kellems
Catalog # [CS8369L](#)



Economy, Receptacle, 50A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal

Features

- 50A 3-Phase Delta 250V AC
- 3-Pole 4-Wire Grounding
- Non-NEMA
- Screw Terminal

Application

Heavy Duty Industrial

General

Catalog Number	CS8369L
Color	Black
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Insulation	Insulated Body
Item Type	50A Single Armored Heavy Duty Receptacle
Material	Composite
Material - Mounting Hardware	Cord Mounted
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Style	Heavy Duty
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact, -25° with impact.
Type	Receptacle
UPC	783585320755

Dimensions

Dimensions	3.30 in x 2.10 in x 2.40 in
Display Size	Standard

Height	2.4 in
Length	3.3 in
Width	2.1 in

Electrical Ratings

Amperage Rating	50 A
Connectivity	Screw Terminals
Current Amperage Description	50 Amp
Current Rating	50 A
Voltage Rating	3 Phase 250 VAC
Voltage Rating Description	3 Phase 250V AC

Conductor Related

Conductor Range	#6 AWG
Number Of Wires	4-Wire
Number of Conductors	4-Wire Grounding
Wire Size	#10 AWG to #4 AWG

Certifications And Compliance

Industry Standard(s)	WR Rating
----------------------	-----------

Logistics

Carton Quantity	30
Pallet Quantity	2340

Product Assets

[Catalog Page - BRY H-21 Catalog Page](#)
[Catalog Page - BRY Q-18 Catalog Page](#)
[Engineering Drawing - CS8369L AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2303_INSTALLINST](#)
[Sales Drawings - WDK_CS8369L_DRAWING_PDF](#)
[Specifications - CS8369L](#)