Incandescent Lampholders, Medium Base

			
Catalog Number	**RL124***	**RL124H**	**RL202**
Description	Pigtail Medium Base Socket with 6 inch Leads, Rubber with #18 Gauge Wire.	Phenolic Medium Base Socket with Hook, Insulation Piercing Termination.	Medium Lampholder to Lampholder Adapter, Pull Chain with Two 2-Prong Outlets without Ground.
Rating	660W 250V	660W 250V	660W 125V 15A 125V

*Note: *cCSAus Certified only.*

Incandescent Adapters, Medium Base



				
Catalog Number	**RL150**	**RL154**	**RL200**	**RL201**
Description	Medium to medium base extension, Screw-in, E26 to E26 socket.	Mogul to medium base adapter, Screw-in E39 to E26 socket.	Outlet Adapter, 2 Prong Plug to Medium Lampholder.	Medium Lampholder Adapter, Medium Lampholder to Outlet without Ground.
Rating	250W, 250V	660W, 250V	15A 660W 125V 15A 125V NEMA 1-15R	15A 125V NEMA 1-15R

Lamp Switches

				
Catalog Number	**RL120**	**RL121**	**RL122**	**RL125**
Description	Pull chain switch, 2 circuit, L1/L2/L1+L2/off.	Pull chain switch, SPST on/off.	Pull chain switch, L1/L2/L3/off.	Rotary switch, SPST on/off.
Rating	6A 125V AC, 3A 250V AC, 3A 125V "L"	6A 125V AC, 3A 250V AC, 3A 125V "L"	6A 125V AC, 3A 250V AC	6A 125V AC, 3A 250V AC, 3A 125V "L"

Note: 6 inch wire leads are #18 AWG AWM/TEW 105°C 600V.

Snap-in Receptacles

		
Catalog Number	**RR374**	**RR374W**
Description	Single receptacle, Black.	Single receptacle, White.
Rating	15A 125V, 3 wire NEMA 5-15R	15A 125V, 3 wire NEMA 5-15R

- Accommodate panel thickness of .031 to .062 inch (0.7 to 1.5 mm)
- Panel cutout .95 x .95 inch (24.1 x 24.1 mm)
- #14 AWG 6 inch AWM/TEW FT1 105°C 600V on black and white leads
- #14 AWG 6 inch AWM/TEW FT1 600V on green lead

Dimensions in Inches (mm)