

Eaton 170M3812D

Catalog Number: 170M3812D

Eaton Bussmann series high speed square body fuse, 100 A, 690 V (IEC), 700 V (UL), , Size 1, Combination fuse status indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3812D
	UPC
	051712334112
EAN	Product Length/Depth
5027590450126	135 mm
Product Height	Product Width
64 mm	40 mm
Product Weight	Warranty
423 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

100 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Current type

AC

Class

Class aR

Clearing (I₂T)

2600 at 660 V

Watt losses

10 W

Fuse shape

Square body, knife blade contacts

Pre arc (I₂T)

360

Color

None

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA NH-style, high-speed dual indicator fuselinks](#)

[CE NH-style, high-speed dual indicator fuselinks](#)

Technical data sheets

[720101 DIN 43620 690V Dual ind](#)

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

1

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia