

Eaton 170M6499

Catalog Number: 170M6499

Fuse-link, high speed, 1100 A, AC 1250 V, size 3, 76 x 92 x 91 mm, aR, IEC, UL, type K indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6499
	UPC
	051712264297
EAN	Product Length/Depth
5996516019559	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Warranty
1357 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated



Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1100 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

3

Rated voltage AC

1250 V

Center-to-center distance of connections

91.4 mm

Current type

AC

Mounting dimension

M12

Class

Class aR

Clearing (I²T)

2800000 at 1000 V, 3600000 at 1250 V

Watt losses

140 W

Fuse shape

Square body, flush end contacts

Catalogs[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)[Bussmann series complete full line catalog no. 1007](#)[170M6499~Eaton Bussmann series high speed square body fuse](#)**Installation videos**[Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications \(brightcove.net\)](#)**mCAD model**[U0773R.stp](#)

Pre arc (I2T)

575000

Color

None

Interrupt rating

100 kAIC

Fitted with:

Type K Indicator for micro

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse type

Flush end

BKN/90 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia