

Specifications



Eaton 170M7156

Fuse-link, high speed, 3000 A, AC 1000 V,
size 4, 120 x 105 x 89 mm, aR, IEC, type K
indicator

General specifications

PRODUCT NAME	Eaton Bussmann series high speed square body fuse
CATALOG NUMBER	170M7156
UPC	051712295277
EAN	5996516021347
PRODUCT LENGTH/DEPTH	89 mm
PRODUCT HEIGHT	120 mm
PRODUCT WIDTH	133 mm
PRODUCT WEIGHT	2689 g
WARRANTY	Not Applicable
COMPLIANCES	Contact factory RoHS Compliant
GLOBAL CATALOG	170M7156
PRODUCT TYPE	High speed square body fuse

Product specifications

AMPERAGE RATING	3000 A
BREAKING CAPACITY	200 kA
FUSE INDICATOR	Centre fuse status indicator
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	4
RATED VOLTAGE AC	1000 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	89.4 mm
CURRENT TYPE	AC
MOUNTING DIMENSION	M10
CLASS	Class aR
CLEARING (I2T)	28000000 at 1000 V
WATT LOSSES	380 W
PRE ARC (I2T)	4700000
COLOR	None
INTERRUPT RATING	200 kAIC
CONSTRUCTION SIZE	4
MOUNTING METHOD	Flush
PACKAGING TYPE	Standard
VOLTAGE RATING	1000 V (IEC)
TYPE	Fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
FUSE TYPE	Flush end SBKN/90 Type K indicator
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

Resources

	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf
CATALOGS	170M7156~FUSE 3000A 1000V 4SBKN/90AR Bussmann series complete full line catalog no. 1007
MANUALS AND USER GUIDES	High speed fuses application guide
MCAD MODEL	eaton-hs-square-body-fuses-mcad-3d-models-u0088.stp
PRODUCT NOTIFICATIONS	eaton-bussmann-series-ukca-marking-high-speed-fuses-pcn-bur-00167-en-gb.pdf eaton-bussmann-series-170m-fuses-product-change-notice-pcn-bur-00193-en-us.pdf
TECHNICAL DATA SHEETS	170M Size 4 Flush end fuses 1000 VAC (IEC and IEC/UL)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

