

# Eaton 25D27Q

Catalog Number: 25D27Q

Eaton Bussmann series LV D fuse, Fast-acting, 500V, 25A, 50 kAIC, Non Indicating, Class gR, Holder, yellow



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage D fuse	25D27Q
	<b>UPC</b>
	051712833165
<b>EAN</b>	<b>Product Length/Depth</b>
5027590470094	50 mm
<b>Product Height</b>	<b>Product Width</b>
22 mm	22 mm
<b>Product Weight</b>	<b>Warranty</b>
31.12 g	1 year limited
<b>Compliances</b>	<b>Certifications</b>
CE Marked	VDE
RoHS Compliant	IEC 60269
	DIN EN 60269-3 (VDE 0636 Part 30)
	DIN EN 60269-1 (VDE 0636 Part 10)
	DIN VDE 0636-301

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Special features

Fast-acting

### Application

For domestic and general industrial applications

### Amperage Rating

25 A

### Fuse size

DII

### Breaking capacity

50 kA

### Construction size (fuse inserts)

DII

### Rated voltage AC

500 V

### Class

Class gR

### Fuse type

D27Q - Fast acting

### Accessory/spare part type

25GD27 Yellow screw cap gauge piece

### Utilization category

gR (general purpose semiconductor protection)

### Color

Yellow

### Interrupt rating

50 kAIC

### Fuse indicator

Non-indicating

### Connection

Other

### Construction

D2

### Construction size

## Resources

### Brochures

[eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf](#)

### Catalogs

[CA134002EN](#)

[Bussmann series complete full line catalog no. 1007](#)

[25D27Q-Eaton Bussmann series low voltage D fuse](#)

### Compliance information

[UKCA Bottle fuse-links, holders, carriers and accessories](#)

[CE Bottle fuse-links, holders, carriers and accessories](#)

### Sales notes

[Product change notification PCN\\_BUR\\_00188](#)

### Technical data sheets

[4124 D and D0 fuses, bases and accessories](#)

DII

Fuse shape

Bottle

Response time

Fast-acting

Suitable for

E27/DII Fuse base

TFD27 Fuse base screw fixing

SFRD27 Fuse base DIN-Rail mount

TFRD27 Fuse base DIN-Rail mount

Material

White ceramic body

Mounting method

Holder

Packaging type

Standard

Release characteristic

Fast (F)

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)