

Specifications



Photo is representative



Eaton BAF-6

Eaton Bussmann series BAF fuse, Fast acting, 6 A, Non-indicating, Ferrule end x ferrule end, 200 AIC at 250 Vac, 10 kAIC at 125 Vac, Nickel-plated brass endcaps, Standard, 250 V

General specifications

PRODUCT NAME	Eaton Bussmann series BAF fuse
CATALOG NUMBER	BAF-6
UPC	051712320061
EAN	5027590056861
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.25 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked
PRODUCT TYPE	Fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	6 A
INTERRUPT RATING	200 AIC at 250 Vac 10 kAIC at 125 Vac
VOLTAGE RATING	250 V

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Silver-plated fuse caps, replacement for "F15B" fuses

Physical details

MATERIAL	Nickel-plated brass endcaps
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BAF-6
TECHNICAL DATA SHEETS	BAF-6~BUSS MIDGET FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

