

Specifications



Photo is representative



Eaton BK/C518-5-R

Eaton C518 Series Fast-acting fuse 5A, 250 Vac, 32 Vdc (self certified), BK-C518-5-R

General specifications

PRODUCT NAME	Eaton Bussmann series C518 fast-acting fuse
CATALOG NUMBER	BK/C518-5-R
UPC	051712640954
EAN	5027590211963
PRODUCT LENGTH/DEPTH	91 mm
PRODUCT HEIGHT	5 mm
PRODUCT WIDTH	5 mm
PRODUCT WEIGHT	4.5 g
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
GLOBAL CATALOG	BK/C518-5-R



Powering Business Worldwide

Product specifications

USED WITH	Axial leads
AMPERAGE RATING	5 A
INTERRUPT RATING	200 AIC at 250 Vac 10 kAIC at 125 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	60 min at 135%, 2 sec at 200%
MATERIAL	Glass tube Nickel-plated brass end cap construction
QUANTITY	100
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - BK/C518-5-R](#)

TECHNICAL DATA SHEETS [C518 2AG 5 mm x 15 mm Fast-acting glass tube fuses](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

