

Specifications



Photo is representative



Eaton BK/GMA-250-R

Eaton GMA Series Fast-acting fuse 0.250A, 250 Vac, 32 Vdc (self certified), BK-GMA-250-R

General specifications

PRODUCT NAME	Eaton Bussmann series GMA Fast-acting glass tube fuse
CATALOG NUMBER	BK/GMA-250-R
UPC	051712647274
EAN	5027590254618
PRODUCT HEIGHT	20 mm
PRODUCT DIAMETER	5.2 mm
PRODUCT WEIGHT	0.7 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
PRODUCT TYPE	5 x 20 mm Fast-acting glass tube fuse



Powering Business Worldwide

Product specifications

USED WITH	out axial leads
AMPERAGE RATING	0.250A
INTERRUPT RATING	35 AIC at 250 Vac 10 kAIC at 125 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	60 min at 135%, 2 min at 200%
MATERIAL	Silver-plated brass endcap construction Glass tube
QUANTITY	100
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/GMA-250-R
	Eaton GMA time delay glass tube fuses data sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

