

Eaton C10G4

Catalog Number: C10G4

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 4 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G4
	UPC
	051712754231
EAN	Product Length/Depth
5027590493543	38 mm
Product Height	Product Width
10 mm	10 mm
Product Weight	Warranty
8.2 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

Type

fuse

Application

for industrial applications
for general purpose use

Amperage Rating

4 A

Fuse size

10 x 38 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

C10G

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

0.7 W

Connection

Ferrule end x ferrule end

Construction size

10 mm x 38 mm

Fuse shape

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)[CA134002EN](#)[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)[UKCA C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia