

Eaton C10M20

Catalog Number: C10M20

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 20 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10M20
	Model Code
	CYLINDRICAL FUSE 10 x 38 20A AM 400V AC
UPC	EAN
051712754613	5027590493680
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Warranty	Compliances
1 year limited	CE Marked
	GoST-R
	RoHS Compliant
Certifications	
IEC 60269	

defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
Application	CA134002EN
motor protection for industrial applications	Bussmann series complete full line catalog no. 1007
Amperage Rating	Compliance information
20 A	UKCA C08G, C08M, etc cylindrical fuselinks
Fuse size	CE C08G, C08M, etc cylindrical fuselinks
10 x 38 mm	Technical data sheets
Current type	720115 Cylindrical fuses
AC	
Breaking capacity	
120 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated voltage AC	
400 V	
Class	
Class aM	
Fuse type	
C10M	
Utilization category	
aM (switchgear protection)	
Fuse indicator	
Other	
Watt losses	
0.96 W	
Connection	
Ferrule end x ferrule end	
Construction size	
10 mm x 38 mm	
Fuse shape	

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

400 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia