

Eaton C10M8

Catalog Number: C10M8

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 8 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10M8
	Model Code
	CYLINDRICAL FUSE 10 x 38 8A AM 500V AC
UPC	EAN
051712754576	5027590493741
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Warranty	Compliances
1 year limited	RoHS Compliant
	CE Marked
Certifications	
IEC 60269	

defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
Special features	CA134002EN
Breaking Capacity 120 kA, Power Loss 0.52 W	Bussmann series complete full line catalog no. 1007
Application	Compliance information
motor protection	UKCA C08G, C08M, etc cylindrical fuselinks
for industrial applications	CE C08G, C08M, etc cylindrical fuselinks
Amperage Rating	Technical data sheets
8 A	720115 Cylindrical fuses
Fuse size	
10 x 38 mm	
Current type	
AC	
Breaking capacity	
120 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated voltage AC	
500 V	
Class	
Class aM	
Fuse type	
C10M	
Utilization category	
aM (switchgear protection)	
Fuse indicator	
Other	
Watt losses	
0.52 W	
Connection	
Ferrule end x ferrule end	
Construction size	

10 mm x 38 mm

Fuse shape

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Mounting method

Holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia