

Eaton C14G6S

Catalog Number: C14G6S

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 6 Amps, 120 kA Breaking capacity, class gG/gL, with striker, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G6S
	Model Code
	CYL FUSE >STR >14 x 51 6A GG 690V AC
UPC	EAN
051712668293	5027590494175
Product Length/Depth	Product Height
51 mm	14 mm
Product Width	Product Weight
14 mm	20.6 g
Warranty	Compliances
1 year limited	RoHS Compliant
	CE Marked
Certifications	
IEC 60269	

Product specifications

Current type

AC

Suitable for

CH14 Modular fuse holder

Mounting method

Holder

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Amperage Rating

6 A

Frequency rating - max

62 Hz

Fuse type

C14G

Fitted with:

Striker

Fuse size

14 x 51 mm

Voltage rating

500 V

Fuse indicator

Top fuse status indicator

Special features

Striker

Construction size

14 mm x 51 mm

Rated voltage AC

500 V

Connection

Ferrule end x ferrule end

Quantity

10

Material

Ceramic

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Utilization category

gG (cable protection/equipment protection)

Watt losses

1.15 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class C gL/gG

Application

for industrial applications

for general purpose use

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia