

Eaton C14G8

Catalog Number: C14G8

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 8 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G8
	UPC
	051712589918
EAN	Product Length/Depth
5027590494182	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Compliances
20.8 g	RoHS Compliant
	CE Marked
	GoST-R
Certifications	
IEC 60269	

defaultTaxonomyAttributeLabel

Resources

Type

fuse

Application

for industrial applications

for general purpose use

Amperage Rating

8 A

Fuse size

14 x 51 mm

Current type

AC

Breaking capacity

80 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

690 V

Class

Class C gL/gG

Fuse type

C14G

Utilization category

gL/gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

1 W

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Fuse shape

Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

[CE C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia