


Eaton C22G80

Catalog Number: C22G80

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 80 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C22G80
	UPC
	051712754507
EAN	Product Length/Depth
5027590495561	58 mm
Product Height	Product Width
22.2 mm	22.2 mm
Product Weight	Warranty
55 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

defaultTaxonomyAttributeLabel

Type

fuse

Application

for industrial applications
for general purpose use

Amperage Rating

80 A

Fuse size

22 x 58 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

C22G

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

7.8 W

Connection

Ferrule end x ferrule end

Construction size

22 mm x 58 mm

Fuse shape

Resources

Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

[CE C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CH22 Modular fuse holder

Material

Ceramic

Mounting method

22 x 58 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)